

2

# Small Cell Concealments Product Guide

Company	
About Raycap	4
Facilities & Capabilities  Manufacturing Facilities  Testing & Measurement  Quality Inspection	6
Electrical Safety Distribution Equipment Compliance	8
Pole Products  Raycap Small Cell Poles  Fully Concealed  Concealed & Non-Concealed  Foundation, Integration, and Colour Options  Proprietary 5G mmWave Materials	10 11
Pole Mounted Infrastructure Invisiwave 5G mmWave Solutions Pole Toppers Side & Mid-pole Mounted Solutions Equipment Mounts & Hardware	15 - 16
Solutions Next to Poles  Enclosures Next To Existing Poles	24 - 25
Building & Rooftop Solutions  Wall or Building Mounted  Rooftop Solutions  Building & Rooftop Solutions Gallery	27
Power Management Solutions AC Disconnects	28 - 32
Fibre Management Solutions Fibre Management	33 - 34

# Company

# About Raycap

Raycap is a global solutions provider with a clear vision of the future network, a result of many years of research and development in the telecommunications field and our continuous engagement with the leading companies in our industry, including partners, customers, suppliers, current and future stakeholders of the network. We have proven to be a thought-leader in the development of telecommunications infrastructure, and our edge is in the design of high throughput, high-density, and multi-technology passive solutions. We possess a unique capability to quickly turn concepts and innovative ideas into industrialized, cost-efficient products, providing realistic solutions and support in any network infrastructure.

Twenty-five years ago, the telecommunications landscape was much different than today – cell phones were larger, smart phones were non-existent, and society was not connected by technology 24-hours a day, seven days a week. Since then, the industry has grown immensely with new equipment and increased demand from mobile operators for more expanded and hardened networks. The latter necessitates the installation of numerous apparatus such as remote radio heads, small cells, antennas, and microwave links located on tower tops, rooftops, and even at street level, which must be concealed.

Raycap has one goal in mind: to provide our customers the best design, R&D, engineering, manufacturing, and sales support to be a one-stop-shop for customers looking to build out their next-generation networks.

# Facilities & Capabilities

# Manufacturing Facilities

### Facilities in Drama, North Greece

A 30,000m<sup>2</sup> plant with engineering, product development, manufacturing, assembly and testing facilities, plus in house wet paint and powdercoat lines.





# West Coast Facility, Post Falls ID A 10,300m<sup>2</sup> plant with engineering, product development, manufacturing, assembly, and testing facilities.



East Coast Facilities, Charleston SC and Kearny NJ 27,400m<sup>2</sup> fabrication and integration facilities with full steel and composite fabrication capabilities plus in house wet paint and powdercoat lines.



Our complete in-house design and manufacturing facilities have the capacity to produce more than 1,000 small cell, concealed or unconcealed poles per month. We provide our customers with:

- R&D Expertise
- Product Design
- Electrical and RF Engineering
- Metal Fabrication and Forming
- Cutting
- Welding
- Drilling
- Wet painting and powder coating lines

- Equipment Integration and Cabling
- Trouble Free Commissioning and Activation
- Assembly
- RF Testing
- Thermal Testing
- Fiber Optic Testing
- Electrical Testing
- Warehousing, Crating, Shipping







# Testing & Measurement

Raycap conducts measurements for its North American products in an RF (radio-frequency) anechoic chamber at its partner's facilities in San Antonio, Texas. Southwest Research Institute (SwRI) and Raycap have a 10+ year testing history, managing demanding testing requirements. RF propagation through concealment material has been critical for wireless service providers as concealment should not compromise the signal quality and service level. Because of this, Raycap has significantly invested in signal generators, network analyzers, beam forming transmitters, and PIM analyzers. All results are recorded for every material that is considered for concealment solutions. Raycap has also developed RF propagation models based on measurements for several frequency bands and therefore is in a position to define, with details, the RF performance in any spectrum region.

### **RF Test Capabilities**

RF insertion loss testing for all commonly used frequencies from 700 MHz to 100 GHz, including detailed pattern impact testing at mmWave frequencies.

10+ year testing history with Southwest Research Institute (SwRI) in San Antonio, TX on all concealment materials used.

### **ENV Test Capabilities**

Experience in the field of environmental testing according to UL, NEBS, GR, ISO, EN, MIL, ASTM standards.

Project scope for poles defined and initiated with UL, RTP:


UL Project Number 4788755381, Product Category NWGQ

Complete UL Listing expected Q3, 2019

Verification of initial cooling (active – passive) performance simulations and actual measurements for low noise level requirements (below 40dBA).

Supervised anti-vandalism tests according to DIN ENV 1627 (RC2/WK2 burglar resistance tests).









# Quality Inspection

Quality inspection is of fundamental importance before any solution is dispatched. Performing all measurements in a controlled environment guarantees less complications during field installation and minimizes commissioning and activation time. For the integrated poles, we conduct several inspections of every cable line:

- RF quality measurements (VSWR, PIM)
- Fibre optic quality measurements (OTDR)
- Power quality measurement (continuity, earth leakage, power ON load tests)
- · Quality inspection checklist



Event		Distance	Loss	Reflect.	Slope	Section	T. Loss
		m	dB	dB	dB/km	m	dB
1	-2:3-	101.11	0.073	-49.78	0.213	101.11	0.018
2	-£3-	121.26	0.046	-52.12	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	20.15	0.097
3	=mD-	222.48		-44.72	0.396	101.23	0.182



# **Electrical Safety**

# Distribution Equipment Compliance

The luminaire pole houses a proprietary load distribution centre capable of providing up to 12 branch circuits at 120VAC, or 6 branch circuits at 240VAC. This distribution equipment is also certified to UL67 Panelboards (E479137) and meets the requirements of being Suitable for Service Equipment (SuSE).

As part of the production line testing required under UL 1598, both a Bonding Circuit Impedance test and a Dielectric Voltage-Withstand test have been taken.

Raycap recently completed all the necessary testing as per UL 1598 Standard for Safety. The relevant certificate of compliance is below.

### CERTIFICATE OF COMPLIANCE

Certificate Number 201
Report Reference E48
Issue Date 201

20190826-E483273 E483273-20190813 2019-AUGUST-26

Issued to: RAYCAP INC

806 S Clearwater Loop Post Falls, ID 83854

This certificate confirms that representative samples of LUMINAIRE POLES Model RCP-6X

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: Ul

UL 1598, Luminaires.

Additional Information: See the UL Online Certifications Directory at

https://iq.ulprospector.com for additional information.

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.

Bruce Mahrenholz, Director North American Certification Program

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, pleas contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/

**(III)** 


Page 1 of 1

### Pole Products

# Raycap Small Cell Poles

Raycap's poles are designed for flexibility and can be ordered with pole top or mid-pole equipment shrouds, light arms and luminaires, mounts, and other hardware. In addition, power and fibre connectivity and power management solutions can be included to enable easy integration and provide protection from electrical overvoltages. No matter your rollout needs, Raycap has the right solution for you.

Hand-holes, doors, internal and external base plates shown for reference and can be engineered per customer custom order. Final configurations to be determined by pole loading and equipment layout.



### Radio Technology

Small cell poles are designed to customer specifications and delivered fully integrated and concealed, or in any format upon request. Raycap designs can accommodate all radio technologies with many available toppers and shrouds.

### Light Arms & Shrouds


Customers can order pole solutions with optional lighting arms, mid-pole shrouds, or attachments to match surrounding light poles. Poles can be designed and engineered to re-use existing luminaires, reducing site costs and lead time.

### Bases

Raycap provides decorative bases to be installed around existing poles to hold and conceal power, fibre distribution, and radio equipment. Structural bases are also available and can support an existing or new light pole installed on top.

# Fully Concealed

Raycap's fully concealed small cell poles are built to meet certain specifications and maintain maximum RF performance. They are designed for flexibility, performance and aesthetics. We offer pole varieties which can be delivered fully integrated, with colour options.



# Concealed & Non-Concealed

Concealed and non-concealed poles are suitable for situations when full concealment is not necessary.












# Optional Pre-Fab Foundation


Raycap can provide customers with traditional poured-in-place foundation designs, as well as alternative pre-fabricated foundation options to help expedite deployment.


Options include:

- Direct Embedded
- Mechanical/Helical
- Pre-Cast
- Break-Away Mechanisms

Contact us directly for more information.







# **Integration Options**

Our broad experience in integration services enables us to help our customers by manufacturing a fully or partially integrated concealed small cell pole product.

Raycap fully integrated concealed small cell poles arrive at a customer's site with cabling, radios, and power/fibre equipment, pre-installed and pre-tested. In the case of fully integrated poles, all that is needed for installation is to set the pole on the foundation, then hook up the feed lines for power and fibre. This is a much faster solution than the traditional method of hiring field crews to install electrical components and run cabling. Taking advantage of Raycap's expertise in integration saves customers time and money.

# Pole Colour Options















**RAL 6012** 

RAL 7022

**RAL 7013** 

**RAL 7040** 

**RAL** 7047

RAL 9011

**RAL** 8008

RAL Color	Description	
6012	Black Green	
7022	Umbra Gray	
7013	Brown Gray	
7040	Window Gray	
7047	Telegray	
9011	Graphite Black	
8008	Olive Brown	

Custom colours available upon request

# Proprietary 5G mmWave Material



Raycap has performed extensive research and testing in the frequency ranges of 28GHz, 37GHz, 39GHz, and up to 52GHz bands to produce its InvisiWave material that is suitable for the concealment of 5G mmWave systems in the U.S. market. These higher frequency applications are much more sensitive to concealment materials being placed in the antenna path.

After nearly a year of problem-solving and testing, and with input and approval from industry stakeholders, the Raycap team has a solution that meets the concealment needs of next generation small cell networks.

In order to validate performance and determine the best possible materials for different concealment applications, all candidate materials were subjected to an array of tests and ultimately the material has proven to provide the performance needed while still maintaining the qualities needed in a good concealment material. The InvisiWave material is available to be used in pole toppers, surrounds and radomes as well as for panel products like chimneys, cupolas and other rooftop concealments.

- Covers and hides mmWave equipment attached to poles or other structures without interfering in performance
- Fabricated from RF friendly, 3mm material
- Easy to install
- Tested from 700MHz to 52GHz
- Features minimum dB loss
- Thoroughly tested to identify beamforming impact
- · Hydrophobic surface
- Compatible to back lobe mitigation techniques with use of upgrade kits
- · Patent pending design
- Custom sizes available based on a case by case basis
- · Materials are approved for smooth textures only
- Field painting is not recommended but film textures are available
- Radomes are all one-piece with a 14" 36" diameter range and can be up to 10' tall
- · Radomes require continuous rolled ring bulkheads for proper attachment
- Patented material

InvisiWave Technical Specifications				
Property	Method	Units	Value	
Thickness		mm	3	
Density	ASTM D-792	g/cm8	0.6 +/- 0.02	
Flexural Modules	ASTM D-790	mPa	1600	
Shore Hardness	ASTM D-2240	Shore D	60	
Flammability	UL94		V-0	
Flammability (Smoke Developed)	ASTM E84/ ASTM E2768		10 (550)/7.4ft	
Surface Resistance	ASTM D-257	Ohm	4.1x10 <sup>14</sup>	
Heat Deflection Temperature	ASTM D-648 @ 1.8Pa Load	°C	62	
Coefficient of Thermal Expansion	ASTM D-696	10-5/°C	6.7	
Tested/Approved Spectrum	sub 6GHz, 24GHz, 28GHz and 39GHz			
Flammability Certification	Class 'A' Fire rated – City of Los Angeles Dept. of Building & Safety Approved (LARR)			

# Pole Mounted Infrastructure

### Invisiwave 5G mmWave Solutions

### 4G + 5G Pole Toppers For Wood or Metal Poles

### RTR-1044-IW

- Covers, hides from sight radios attached to poles or other structures without interfering in radio performance
- Fabricated from RF friendly material
- Tested from low frequencies up to 100 GHz
- · Suitable for concealing mmWave radios
- · Features minimum dB loss
- PIM free tested per IEC 62037-8
- · Thoroughly tested to validate no beam forming impact
- Hydrophobic surface
- Compatible with multiple radio/antenna configurations (mounts supplied per customer-specified combinations)
- Multiple colour options available
- Easy to install
- Includes 5G radio bracket and antenna mount
- Includes pole mounting brackets
- · Fans and controllers included
- Adjustable internal height is configurable to multiple radio/antenna configurations to allow for easy fixture expansion or equipment swaps

# InvisiWave\*



RTR-1044-IW

### REM-5470 for NR AU Radios

- Complete solution for Samsung 5G NR AU radios
- Through bolted connection style; alternative connection types available for different pole styles
- · Accommodates all small cell 4G canister antennas and
- Samsung 5G NR AU radios
- Variable pole diameter attaches to most common sizes
- All structural steel hot dip galvanized per ASTM A123 with optional powdercoated finish to customer colour specification
- Optional RCS-5128 antenna cable shroud for 5G radios\*
  - Provides cable concealment and protection
  - Fabrication fit to radio used
- Fabricated from RF friendly, mmWave friendly material
- Tested from low frequencies up to 100 GHz with minimum dB loss
- Thoroughly tested to validate no beam forming impact
- PIM free tested per IEC 62037-8
- Hydrophobic surface
- Easy to install
- Multiple colour options available



# Pole Toppers

# InvisiWave\*

### For Wood or Metal Poles

Available in a variety of types from 4G only to 4G/5G or 5G only, Raycap Pole Toppers fit onto existing poles and are available in both concealed and non-concealed styles.

Raycap Pole Toppers can be designed with InvisiWave radomes to accommodate 24GHz frequencies.

- Overall-height can be adjusted as required
- Concealment can be designed to various diameters to meet operator and/or municipality requirements
- Can be ordered in various colours to blend in with the surrounding environment





RTR-3733-X 4G & 5G







RTR-1694-IW



RTR-9397-IW

# Pole Toppers

### 4G + 5G Pole Toppers For Wood or Metal Poles

### RTR-2001164-00

- 24" OD partially concealed topper for Ericsson (E///) 6701
- · Standard with down tilt mounts
- · Designed for 8" or 10" Raycap steel pole



### REM-2849-2

- 18" fully concealed for Gamma Nu 4G Omni & E/// 2203
- Clamps on top of wood or steel pole from 5" -10" outside diameter (OD)



### RTR-2001604-00

- 18" OD fully concealed for Amphenol 4G Omni
- Clamps on top of wood or steel pole of 5" 9"
   OD
- · 3° of tilt correction



### REM-5651-IW

- 22" OD fully concealed topper for E/// 6701
- Clamps on top of wood or steel pole of 5" -12" OD
- · No down tilt included



### RTR-2000793-00

- 22.5" OD fully concealed for Samsung 5G and 4G Omni
- Slip fits on top of 9" 10" OD tapered steel pole



### RTR-2100357-00

- · Unconcealed 4G wood pole topper
- · Galtronics 4G Omni
- · Clamps to wood pole 5" 14" OD



### RTR-2100459-00

- 16" OD partially concealed topper for E/// 6701
- · Standard with down tilt mounts
- Designed for Raycap steel pole or REM pole clamp mounts



### RTR-2100828-00

- Unconcealed JMA 4G Omni topper
- Conceals (2) E/// 220x radios within ventilated cable shroud
- Designed for Raycap steel pole or REM pole clamp mounts



### RTR-2100278-00

- · Unconcealed Gamma Nu 4G Omni topper
- Conceals (4) E/// 220x radios within ventilated cable shroud
- Designed for Raycap steel pole or REM pole clamp mounts



### RTR-2101843-00

- 18" Radome for Gamma Nu 4G Omni & E/// 2203
- E/// 2181 5G radio mask combo
- Clamps on top of wood or steel pole of 5"
   14" OD
- · Also bolts to top of Raycap steel poles



Additional designs available upon request

### Side & Mid-Pole Mounted Shrouds

### Pole Mounted Infrastructure

In some locations installation on the ground is not possible. Whether due to lack of space, permit restrictions or even a costly installation of power and/or fibre cables for the connectivity, this scenario requires the installation of active equipment (antennas and connectivity enclosures) on or at the side of an existing structure. We have developed several side mounted solutions for existing light poles as well as additional approaches that can be wall mounted.





### Side Mounted Shrouds

- · Shroud passive vented design
- · Door access design allows easy access
- · Construction:
  - Aluminum cage Stainless steel mast supports
- · Many options and heights available





### Side Mounted 5G Shrouds

- Ergonomic design for easy radio installation and replacement
- Covered with InvisiWave mmWave friendly material
- InvisiWave is tested per UL 746C and meets requirements of an f1 rated material, suitable for outdoor use
- Entire solutions thermally tested according to GR-487
- Includes fibre and power management
- Offset bracket to minimize signal blockage components
- Supports various configurations
- Mount secures with bolts around top of pole
- · Many colour finishes





### Pole Collar

- · Antenna Top-Mount
- · Mount secures with bolts around top of pole
- · Many colour finishes

# Mounts & Hardware

# Equipment Mounts & Hardware

### 4G + 5G Wood Pole Top Mount Solutions

Raycap offers pole mount hardware for easy installation of equipment on existing poles. They are specifically designed for fast installation and easy access.

- RTR Series Accommodates all small cell 4G panel antennas through various adapter plates
- Variable pole diameter attaches to most common sizes
- All structural steel powder-coated galvannealed finish to customer colour specification
- PIM free tested per IEC 62037-8
- Included bubble-level assists in precise and easy installation
- Universal wood pole base or custom metal pole base available
- Each unit ships with the RTR-Series Universal Top-Mount Base



### 4G + 5G Wood Pole Side-Mount Solutions

- RSM Series Accommodates all small cell 4G panel antennas through various adapter plates
- Variable pole diameter attaches to most common sizes
- All structural steel powder-coated galvannealed finish to customer colour specification
- PIM free tested per IEC 62037-8
- Included bubble-level assists in precise and easy installation
- Universal wood pole base or custom metal pole base available
- Each unit ships with the RSM-Series Universal Side-Mount Base



Also available with fiberglass tube extension to support ConEdison specifications.

RSM-FXGL



### RSM-CMM



RSM-CMM-PA



### 4G + 5G Wood Pole Top Mount Solutions

Our modular series offers nearly endless combinations that can be made with a set of modular components. Available options are not limited to the below pre-built assemblies. All common OEMs are supported.

- Can be employed to fit almost any custom equipment configuration
- Accommodates all 5G mmWave radios or small panel, whip, or canister 4G antennas
- Variable pole diameter attaches to most common sizes
- All structural steel hot dip galvanized per ASTM A123 with optional powder coated finish
- Integrated leveling is provided in three axes for all technologies, and bulls-eye leveling dots are included.



### **Connection to Pole**

- M-22922 Base component for most topper and side arm assemblies, two universal mounting patterns
- 2 M-22080 Base component, single universal mounting pattern
- 3 M-22780 Triple clamp assembly, 7" diameter poles



### Leveling

- 4 M-22062 Light duty leveling for omni-directional whip and canister antennas, up to 5° in any direction
- M-22231 Heavy duty leveling assembly, tall, extra clearance for large 5G radios, up to 10° in any direction
- 6 M-22436 Heavy duty leveling assembly, compact, up to 10° in any direction



### **Equipment Mounting - Radios and Antennas**

- 7 M-22643 Whip antenna mount, bolt
- 8 M-22047 Whip antenna mount, clamp
- 9 M-22858 Omni-directional canister antenna mount
- M-22078 Radio mounting bracket, 10° downtilt, 5° uptilt, supports all major radios



### **Side Arm Options**

- M-22193 Side arm, single-bolt pattern
- 12 M-22291 Side arm extension, universal mounting pattern



### Adapter / Extension


- M-22925 Converts between the universal mounting pattern and single-bolt mount pattern
- M-22585 90° universal mounting pattern adapter, also supports single-bolt pattern
- 6 M-22774 Provides two additional universal mounting locations
- 6 M-22919 For bridging between two legs (M-22922) to support a large topper assembly



### 4G + 5G Modular Component Solutions


### **SINGLE LEG**

Options are for light-duty installations, down to  $5.5^{\circ}$  diameter poles. Mounting via thru-bolts and/or straps.



### **DUAL LEG**

These options support more and larger equipment and up to 13" diameter poles. Mounts via thrubolts and/or straps.



### 4G + 5G Modular Component Solutions

### **TRIPLE CLAMP**

Feature clamping with additional bolt-through option. Fits 7"-13" diameter poles.

REM-M-22081
5G Triple Clamp Assembly



# REM-M-22244 Omni-mount Clamp Assembly

### **SHORT BRACKET**

Mounts via thru-bolts and/or straps.

RSM-M-22815 -Single 5G Radio







### **DOUBLE SIDED**

Equipment mounted on both sides of the pole, thru-bolt and/or strap mounting.

RSM-M-22844
Equipment mounted on both sides of the pole, thru-bolt and/or strap mounting.



### **TALL BRACKET**

With side arm available in multiple lengths. Thru-bolt or strap mounts.



**RSM-M-22162** 5G Mount

RSM-M-22291 —— 5G Side Arm Mount



RSM-M-22227 4G / 5G Side Mount



### 4G + 5G Wood Pole Extension Mounts

### **WOOD MOUNT EXTENSIONS**

### RATM-211501-A

- 4G/5G wood pole solution
- Supports various pole ODs
- Fiberglass extension, bulls-eye leveling dots are included
- Tri-sector mmWave radio mounts with downtilt shown with Samsung AT1K radios technologies



### RATM-211501-ST

- 4G/5G wood pole solution
- Supports various pole ODs
- Fiberglass extension, bulls-eye leveling dots are included
- Dual-sector mmWave radio mounts with downtilt shown with Nokia AEUD/E radios.



Raycap's line of 4G + 5G specialized extension mounts for wood poles provides excellent mounting solutions for various radios or antennas.

Our complete side-mounted hardware series enables the easy mounting of radio and antenna systems to the sides of wood or steel poles.

### SIDE MOUNT SOLUTIONS

### REM-3099

- Side arm mount for 4G Omni and supporting radios
- 5G radios may be banded to the pipe mast as shown with Nokia AEUD/E
- Can be strapped or thru-bolted to wood or steel poles



### REM-1348

- Side mounted enclosure for (3)
- E/// 220x radios
- Fully concealed 4G Omni within radome
- Can be strapped or thru-bolted to wood or steel poles



### RSM-4651-5

- Side mounted enclosure for (3)
- E/// 220x radios
- Elevated radome for 5G radios mounting as shown with E/// 1281
- Can be strapped or thru-bolted to wood or steel poles



### RSM-20247

- Side mount frame for 4G Omni and supporting radios
- 5G radios may be banded to the pipe mast as shown with E/// 1281
- Can be strapped or thru-bolted to wood or steel poles



# Solutions Next To Poles

# **Enclosures Next To Existing Poles**


Raycap has developed a modular small cell cabinet solution that can be seamlessly integrated in various environments. The solution is comprised of two parts; the lower part hosts equipment while the upper part is decorative.

Depending on the equipment (single band, dual band or multiband), there are two (2) sizes for the lower compartment. For the decorative part, there are three (3) variants: plant, recycle bin and map. This modular approach gives customers the flexibility to choose among different configurations and adapt the appearance based on the surrounding environment.

### Planter Box

- Modular design
- Lower compartment contains:
  - Electrical components
  - Fibre optic components
  - Active Equipment
  - Ventilation System
  - Locking mechanism
  - Cable entry system
- Decorative part is a planter box:
  - Easy detachment
  - Drainage system available
  - Plastic or real plants to be considered





# Enclosures Next To Existing Poles













# **Building & Rooftop Solutions**

# Wall or Building Mounted

Product solutions covering rooftop small cell sites with screen walls or side-mounted boxes of all sizes are available from Raycap. Rooftop or wall side-mounted box concealments compliment existing construction, and hand-crafted faux brick, block, stucco, and stone textures seamlessly blend with buildings.


### **Custom Shrouds**

- · Conceal small cell equipment
- Blend into any existing facility
- Round form factor shown; shrouds can be any shape including square, rectangular, or multi-sided
- Multiple operator and 5G/ InvisiWave versions available



### Replica Antennas

- Fabricated from RF friendly InvisiWave
- Covers and hides from sight radios attached to poles or other structures without interfering in radio performance
- Compatible with 5G radios
- Suitable to conceal mmWave radios
- Full range of heights and diameters available to meet virtually all concealment applications
- Compatible to back lobe mitigation techniques with use
- Easy to install



# **Rooftop Solutions**

Ballasted (non-penetrating) concealment pods are a great solution for disguising rooftop antennas. The ballasted pods are comprised of a steel frame, centre mast pipe, steel clamp-on bulkheads and a radome. These standard frames allow for reduced engineering cost and lead time plus the optimized framing material makes manufacturing and installation a breeze.

### **Ballasted Pods**

- 5G InvisiWave version available
- Does not require roof penetrations
- Can be used as temporary solution
- Easily to assemble and install



### Screen Walls

- Screen walls hide rooftop equipment
- The exterior can be factory colored or painted, if InvisiWave, or textured if StealthSkinTM to blend into any building
- Screens can include an InvisiWave panel to accommodate 5G radios
- Many options to choose from





# **Building & Rooftop Solutions Gallery**













# **Power Management Solutions**

### **AC Disconnects**

The RSCAC and RSx-Series are 120/240 VAC industry-standard load centres and surge protection devices suitable for use as service equipment (SUSE) with NO conditions per UL and NEC.

Designed to provide robust overvoltage surge protection for the AC power circuits for today's small cell radio systems, they employ patented Strikesorb® 30-A-2CHV modules capable of withstanding direct surge currents up to 5kA (10/350 µs) and induced surge currents up to 60 kA (8/20 µs).

This product line provides dual (Line 1 to Neutral) (Line 2 to Neutral) protection for up to sixteen AC circuits depending on the model.

### Common and Standard Features

- Suitable for use as Service Equipment SUSE with NO condition per UL and NEC
- 120/240 VAC, up to 100A installations
- Load breakers can be 2A 25A rated (RSx-Series) or 15A and 20A Tandems (RSCAC-Series)
- Tightly integrated AC disconnect, AC distribution and AC surge protection in one cabinet
- Strikesorb Over Voltage Protection (OVP) on AC circuits
- Ruggedized industrial construction, most with top and bottom cable access for maximum flexibility and space-savings in small cell deployments
- Rigorous weatherproof enclosure options: NEMA 4 (for hose down/sprinkler protection), Nema 4x (for corrosive locations) and even NEMA 6/6p (IP68) for temporarily submerged locations like street hand holes
- Optional AC GFI protected outlet and/or various means of external disconnects available on some models







RSD-FMC-Z16MS-21NN (16 Breakers, Strikesorb SPD, External Disconnect)

### RSCAC-1333 Series

- 60A main breaker
- 22kA Fault Current Rating (kAIC)
- 6x configurable tandem breakers provided (12 Loads) (Default is 6x 15A/15A tandem breakers. Custom breaker lists can be specified at the time of order.)
- Bottom cable-access
- 9"H x 9"W x 5"D NEMA 4X or IP 68
   & NEMA 6/6P rated enclosure
- · Versatile mounting bracket included



RSCAC-1333-P-240



RSCAC-1333-P-240-D

Hinged-CoverExternal Disconnect



RSCAC-1333-PH-240

- No-hinge front door for concealment or pole applications
- Submersion up to 1 meter for 30 minutes

### RSCAC-9556 Series

- 100A main breaker
- 22kA Fault Current Rating (kAIC)
- 6x configurable tandem breakers provided (12 Loads) (Default is 6x 15A/15A tandem breakers. Custom breaker lists can be specified at the time of order.)
- Bottom cable-access
- 11"H x 9"W x 5"D NEMA 4X or IP 68
   & NEMA 6/6P rated enclosure
- · Versatile mounting bracket included



RSCAC-9556-P-240



RSCAC-9556-P-240-D

Hinged-Cover
 External Disconnect



RSCAC-9556-PH-240

- No-hinge front door for concealment or pole applications
- Submersion up to 1 meter for 30 minutes

### RSCAC-9550 Series

- 60A main breaker
- 22kA Fault Current Rating (kAIC)
- 6x configurable tandem breakers provided (12 Loads) (Default is 6x 15A/15A tandem breakers. Custom breaker lists can be specified at the time of order.)
- Top & Bottom cable-access
- 11"H x 9"W x 5"D NEMA 4X or IP 68 & NEMA 6/6P rated enclosure
- · Versatile mounting bracket included



RSCAC-9550-P-240



RSCAC-9550-P-240-D

Hinged-Cover
 External Disconnect



RSCAC-9550-PH-240

- No-hinge front door for concealment or pole applications
- Submersion up to 1 meter for 30 minutes

### RSCAC-7038 Series

- 100A main breaker
- 10kAIC System Rating (due to GFI)
- 6x configurable tandem breakers provided (12 Loads) (Default is 6x 15A/15A tandem breakers. Custom breaker lists can be specified at the time of order.)
- Top & Bottom cable-access
- 14"H x 9"W x 5"D NEMA 4 rated enclosure
- GFI Convenience Outlet



RSCAC-7038-P-240



RSCAC-7038-P-240-D

- Hinged-Cover
External Disconnect



### RSCAC-7239 Series

- 100A main breaker
- 22kAIC System Rating
- 6x configurable tandem breakers provided (12 Loads) (Default is 6x 15A/15A tandem breakers.
   Custom breaker lists can be specified at the time of order.)
- Top & Bottom cable-access
- 14"H x 9"W x 5"D NEMA 4 rated enclosure



RSCAC-7239-P-240



RSCAC-7239-P-240-D



### RSCAC-1440-P-240

- 60A main breaker
- DC power supply capable of providing up to 2 x 600 Watts at -54VDC
- (2) 15A DC outputs
- Passive or active cooling
- Indicator LEDs for AC available (1) and DC available (2)
- NEMA 3R rated enclosure suitable for outdoor
- Field retrofitable from 1 PSU to 2



### **RSx-F Series**

- 16x configurable breakers provided (Load breaker list [ampacities and quantities total 16] to be specified at the time of order.)
- 60A or 100A Main Breaker
- 10kA Fault Current Rating (kAIC)

- Top, bottom and side cable/conduit access
- 18.5"H x 9"W x 6"D NEMA 4 powder-coated enclosure, available in many colors
- Versatile mounting bracket included







RSD-FMC-Z16MS-21NN (16 Breakers, Strikesorb SPD, External Disconnect)

### Model Number Configuration

# RSa-FMb-c16MS-21NN

a: RAL color				
D		= Light Gray / RAL7047		
G		= Green / RAL6012		
В		= Black / RAL9011		
N		= Brown / RAL5022		
L		= Blue / RAL5005		

	LED & Ext. Disconnect
N	= None
L	= Light and External Disconnect

	c: Main Breaker
Х	= 60A Main Breaker
Z	= 100A Main Breaker

Disconnect Option	s		
	Clolor Options	No External Disconnect	With External Disconnect & Status Ligh
	Light Gray / RAL7047	RSD-FMN-X16MS-21NN	RSD-FML-X16MS-21NN
	Green / RAL6012	RSG-FMN-X16MS-21NN	RSG-FML-X16MS-21NN
60A Main Breaker	Black / RAL9011	RSB-FMN-X16MS-21NN	RSB-FML-X16MS-21NN
	Brown / RAL5022	RSN-FMN-X16MS-21NN	RSN-FML-X16MS-21NN
	Blue / RAL5005	RSL-FMN-X16MS-21NN	RSL-FML-X16MS-21NN
	Light Gray / RAL7047	RSD-FMN-Z16MS-21NN	RSD-FML-Z16MS-21NN
	Green / RAL6012	RSG-FMN-Z16MS-21NN	RSG-FML-Z16MS-21NN
100A Main Breaker	Black / RAL9011	RSB-FMN-Z16MS-21NN	RSB-FML-Z16MS-21NN
	Brown / RAL5022	RSN-FMN-Z16MS-21NN	RSN-FML-Z16MS-21NN
	Blue / RAL5005	RSL-FMN-Z16MS-21NN	RSL-FML-Z16MS-21NN

### Common and Standard Features

- Suitable as Service Equipment (SUSE) with NO condition per UL and NEC
- 60A or 100A Main Breaker
- 120/240 VAC
- Up to 16 circuits available
- Strikesorb 2CHV SPD (L1-N, L2-N)
- Metallic enclosure, NEMA 4
- 9"W x 6"D (Ht depends on Bkrs)
- Versatile mounting bracket included

### **RSx-D Series**

- 60A or 100A Main Breaker, 10kAIC
- NEMA 4 rated Powder Coated Steel enclosure
- Top, btm, side cable-access
- Can ship with Qty=2 to 10 Bkrs



RSD-DMN-X10MS-21NN



RSD-DML-X10MS-21NN

- Hinged-Cover
External Disconnect



RSD-DML-Z16MS-21NN (Lt. Gray colour, 10 Breakers, Strikesorb SPD, External Disconnect)

### **RSx-E Series**

- 60A or 100A Main Breaker, 10kAIC
- NEMA 4 rated Powder Coated Steel enclosure
- Top, btm, side cable-access
- Can ship with Qty=2 to 12 Bkrs



RSD-EMN-Z12MS-21NN



RSD-EML-Z12MS-21NN

- Hinged-Cover

External Disconnect



RSD-EML-Z12MS-21NN (Lt. Gray colour, 10 Breakers, Strikesorb SPD, External Disconnect)

# Fibre Management Solutions

# Fibre Management

Raycap offers pole or wall mount fibre enclosures for indoor and outdoor use. They are specifically designed for fast deployment and easy customer connection, providing the ultimate flexibility and optimal fibre organization.

### Common and Standard Features

- Lightweight design
- IP65 sealing rate
- Minimum bending radius protection 30mm
- Customized configuration capacity available
- Allows integration of passive optical components
- Wall and pole mounted

- UV stable material for outdoor above ground use
- · Passive convection cooling
- The standard kit contents include wall mounting brackets and splice protector sleeves
- Optional installation of 6 PLC splitters\* (PLC splitters are pre-connectorized only on the outputs.)
   Customization available

### RTF-8028

• Splicing capacity of 8 fibres



### RTF-3392

• Splicing capacity of 16 fibres







# Fibre Management

### RTF-5238

• Splicing capacity of 6 fibres





### RTF-3018

• Splicing capacity of 2 fibres





### RTF-7054

• Splicing capacity of 4 fibres





### RTF-3116

• Splicing capacity of 12 fibres





### RTF-8818

• Splicing capacity of 24 fibres





# Multi-Fibre Cables (OMCS-GY-xx-yy-LCLC-zzzM)

- Dielectric rodent protected
- Low smoke, halogen free (FR LSZH) outer sheath
- Connectors: RRH side: Duplex LC BBU side: Duplex LC



# Single Mode / Multi Mode Cables (Duplex Patch cords)

- 0.9/1.8/2.0/3.0mm versions available
- Low loss connectors
- LSZH jacket
- RoHS compliant
- Different boot lengths available



### Notes



# Raycap Worldwide Locations

### Raycap Inc.

806 South Clearwater Loop Post Falls, ID 83854 United States of America

7555-A Palmetto Commerce Pkwy North Charleston, SC 29420 United States of America

46 Sellers Street Kearny, NJ 07032 United States of America

### Raycap GmbH

Parkring 11 85748 Garching Munich Germany

### Raycap S.A.

Telou & Petroutsou 14 15124 Maroussi Athens Greece

Raycap S.A. Manufacturing Industrial Area of Drama 66100 Drama Greece

### Raycap d.o.o.

Poslovna cona Žeje pri Komendi Pod hrasti 7 1218 Komenda Slovenia

### Raycap Cyprus Ltd.

46 Lefkosias Street Industrial Area of Dali 2540 Nicosia Cyprus

### Raycap SAS

84 rue Charles Michels Building B 93200 Saint-Denis France

### Raycap Corporation SRL

4A, Johann Strauss, 4 Floor, Sector 2, 020312 Bucharest Romania

### Raycap (Suzhou) Co. Ltd.

Block B, Phase II of New Sea Union No. 58 Heshun Road SIP, Suzhou 215122 Jiangsu Province China



