DATA SHEET Modular SPD for up to 3 Lines RayDat NSLL-3 LF Series




IEC/EN Category: C1/C3 Voltages: 24 V DC Frequency Range: 1 MHz

Housing: Modular Design Compliance: IEC/EN 61643-21

UL 497B 4th Edition

Configuration:



Technical Data

RayDat NSLL-3-xx LF Series 24

| RayDat NSLL-3-XX LF Series | | | 24 |
|--|---------------|------------------|---|
| Electrical | | | |
| Lines Protected | | | 1 (3 Conductors) |
| Nominal Operating Voltage (DC) | | U _n | 24 V |
| Maximum Continuous Operating Voltage (DC) | | U _c | 30 V |
| Rated Load Current at 40 °C | | IL | 12A |
| Rated Load Current at 70 °C | | IL | 10 A |
| C1 Nominal Discharge Current (8/20 μs) | (Line-Line) | In | 250 A |
| | (Line-Ground) | | 250 A |
| C1 Total Nominal Discharge Current (8/20 µs) | | In | 750 A |
| C3 Voltage Protection Level (1 kV/μs) | (Line-Line) | U _p | 130V |
| | (Line-Ground) | | 65 V |
| Rated Spark Overvoltage | (Line-Line) | | 64V-76V |
| | (Line-Ground) | | 32V-40V |
| Response Time Overvoltage Protection | | t _A | <1 ns |
| Thermal Protection | | | Yes |
| Insulation Resistance of the Protection | (Line-Line) | R _{iso} | > 15 MΩ |
| Serial Resistance per Path | | R | 0.1Ω |
| Capacitance | (Line-Line) | С | typ. 1.5 nF |
| | (Line-Ground) | | typ. 3 nF |
| Maximum Frequency | | f_G | 1 MHz |
| Mechanical | | | |
| Temperature Range | | | -40 °F to +176 °F [-40 °C to +80 °C] |
| Conductor Cross Section (max.) | | | 12 AWG / 4 mm ² (solid) |
| | | | 14 AWG / 2.5 mm ² (flexible) |
| Degree of Protection IEC/EN 60529 | | | IP20 (built-in) |
| Housing Material | | | Thermoplastic; Grey; Extinguishing Degree V-0 |
| Mounting IEC/EN 60715 | | | 35 mm DIN Rail |
| Operating State / Fault Indication | | | Green Flag / Red Flag |
| Order Information | | | |
| Order Code | | | 24 |
| NSLL-3-xx LF | | | 7088.48 |
| NSLL-3-xxM LF (module) | | | 7088.49 |



RayDat NSLL-3 LF Series

Configuration

Legend


DB Diode Block


GDT Gas Discharge Tube

PG Protective Grounding


R Resistor

Dimensions & Packaging





| NSLL-3-xx LF Series | 24 |
|------------------------------------|---------------------------------|
| Dimensions | |
| Weight per Unit | 1.98 oz [56 g] |
| Dimensions DIN 43880 | .24" [6.2 mm] |
| Packaging Dimensions (Single Unit) | 4.72×4.33×0.39" [120×110×10 mm] |
| Minimum Package Quantity | 15 pieces |



| NSLL-3-xxxM LF Series | 24 |
|------------------------------------|---------------------------------|
| Dimensions | |
| Weight per Unit | 0.56 oz [16 g] |
| Packaging Dimensions (Single Unit) | 4.72×4.33×0.39" [120×110×10 mm] |
| Minimum Package Quantity | 15 pieces |
| Minimum Package Quantity | 15 pieces |



Monitoring Unit Transmitter & Receiver available for all product variants. inches [mm]

Information contained in this document is subject to change at any time without notice.





