



Location of Use: Main Distribution Boards,
60 mm Busbar Systems

Network Systems: TT, TN-S

Mode of Protection: L-N, N-PE

IEC/EN: Class I+II / Type 1+2

Housing: Pluggable design

Compliance: IEC 61643-11:2011

EN 61643-11:2012 + A11:2018



Technical Data

ProTec 60 T1H-xxx-3+1(-R)

300

IEC Electrical

Nominal AC Voltage (50/60Hz)	U_o/U_n	240 V
Maximum Continuous Operating Voltage (AC)	(L-N) U_c	300 V
	(N-PE) U_c	305 V
Nominal Discharge Current (8/20 μ s)	(L-N)/(N-PE) I_n	20 kA / 80 kA
Maximum Discharge Current (8/20 μ s)	(L-N)/(N-PE) I_{max}	65 kA / 100 kA
Impulse Discharge Current (10/350 μ s)	(L-N)/(N-PE) I_{imp}	12.5 kA / 50 kA
Specific Energy	(L-N)/(N-PE) W/R	39 kJ/ Ω / 625 kJ/ Ω
Charge	(L-N)/(N-PE) Q	6.25 As / 25As
Voltage Protection Level	(L-N)/(N-PE) U_p	1500 V / 1500 V
Follow Current Interrupt Rating	(N-PE) I_{fi}	100A
Response Time	(L-N)/(N-PE) t_A	< 25ns / < 100ns
Overvoltage Category		III
Maximum Backup fuse, if required		315 A gG
Short-Circuit Current Rating (AC)	I_{SCCR}	25 kA
TOV Withstand 5s	(L-N) U_T	442 V
TOV SafeFail 120min	(L-N) U_T	442 V
Number of Ports		1


Mechanical & Environmental

Operating Temperature Range	T_a	-40 °F to +185 °F [-40 °C to +85 °C]
Permissible Operating Humidity	RH	5%...95%
Pollution Degree		2
Altitude (max)		13123 ft [4000 m]
Terminal Screw Torque	M_{max}	PH2 / 40 lbf·in [4.5 Nm]
Conductor Cross Section (max)		2 AWG (Solid, Stranded) / 4 AWG (Flexible)
		35 mm ² (Solid, Stranded) / 25 mm ² (Flexible)
Mounting		60 mm Busbar Systems
		Width: 12, 15, 20, 25, 30 mm
		Thickness: 5 mm, 10 mm (with removed spacers)
Degree Of Protection		IP 20*
Housing Material		Thermoplastic: Extinguishing Degree UL 94 V-0
Operating State / Fault Indication		Green Flag / Not Green Flag
Remote Contacts (RC)		Optional
RC Switching Capacity		AC: 250V/1 A, 125V/1 A; DC: 48V/0.5 A, 24V/0.5 A, 12V/0.5 A
RC Conductor Cross Section (max)		16 AWG (Solid) / 1.5 mm ² (Solid)
Overvoltage Category		III

*IP 40 (in combination with cover)

Legend


L	Line Busbar Terminal
⏏	PE Conductor Terminal
N	Neutral Conductor Terminal
RC	Remote Contacts Terminal (Optional)
TD	Thermal Disconnect



Order Information

Order Code	300
ProTec 60 T1H-xxx-3+1	515 963
ProTec 60 T1H-xxx-3+1-R (with remote contacts)	515 964
ProTec T1H-xxx-P (plug)	59.C384


Dimensions & Packaging



Complete Unit

ProTec 60 T1H-xxx-3+1	300
Weight	pounds [grams] 1.325 [601]
Packaging Dimensions (HxWxL)	10.6 × 14.8 × 15.5" [270 × 375 × 395 mm]
ProTec 60 T1H-xxx-3+1-R	300
Weight	pounds [grams] 1.340 [608]
Packaging Dimensions (HxWxL)	10.6 × 14.8 × 15.5" [270 × 375 × 395 mm]
Standard Order Quantity	20 Units

Spare Plug



Single Unit

ProTec T1H-xxx-P	300
Weight	pounds [grams] .223 [101]
DIN 43880 Dimension	1 TE / .71" [18]
Packaging Dimensions (HxWxL)	4.3 × 4.5 × 13.8" [109 × 115 × 352 mm]
Standard Order Quantity	28 Units