DATASHEET

Lightning and Overvoltage Protection

ProTec T1SM 4+0

Class I • Class II • Class III • Type 1 • Type 2 • Type 3

25 kA Series



Location of Use: Main Distribution Boards
Network Systems: TN-S
Mode of Protection: L-PE, N-PE
IEC/EN Category: Class I+II+III/Type 1+2+3
Housing: Pluggable Design
Compliance: IEC 61643-11:2025
EN IEC 61643-11:2025

CE RoHS COMPLIANT

Technical Data

ProTec T1SM-xxx-4+0(-R)			275
IEC Electrical			
Nominal AC Voltage (50/60 Hz)		U_o/U_n	240 V
Maximum Continuous Operating Voltage (AC)		U_c	275 V
Nominal Discharge Current (8/20 µs)		I_n	25 kA
Maximum Discharge Current (8/20 µs)		I_{max}	65 kA
Impulse Discharge Current (10/350 µs)		I_{imp}	25 kA
Specific Energy		W/R	156.2 kJ/Ω
Charge		Q	12.5 As
Open Circuit Voltage of Combination Wave Generator (1.2/50 µs)		U_{oc}	6 kV
Short Circuit Current of Combination Wave Generator (8/20µs)		I_{cw}	3 kA
Voltage Protection Level		U_p	1500 V
Response Time		t_A	< 100 ns
Overvoltage Category			III
Overcurrent Protection (max)			315 A gG
Short-Circuit Current Rating (AC)		I_{SCCR}	50 kA
Follow Current Interrupt Rating (AC)	(L-PE)/(N-PE)	I_{fi}	50 kA/100 A
TOV Withstand 120 min	(L-PE)	U_T	442 V
Number of Ports			1
Additional Electrical Parameters *(Tests performed within Raycap testing laboratory only)*			
Residual Voltage at 5 kA (8/20 µs)	(L-PE)/(N-PE)	U_{res}	1200 V/275 V
Minimum Overcurrent Protection, if required			250 A gG
Mechanical & Environmental			
Operating Temperature Range		T_a	-40 °F to +185 °F [-40 °C to +85 °C]
Permissible Operating Humidity		RH	5%...95%
Altitude (max)			13123 ft [4000 m]
Terminal Screw Torque		M_{max}	40 lbf·in [4.5 Nm]
Conductor Cross Section (max)			2 AWG (Solid, Stranded)/4 AWG (Flexible)
			35 mm² (Solid, Stranded)/25 mm² (Flexible)
Mounting			35 mm DIN Rail, EN 60715
Degree of Protection			IP 20 (built-in)
Housing Material			Thermoplastic: Extinguishing Degree UL 94 V-0
Operating State/Fault Indication			Green Flag/Not Green Flag
Remote Contacts (RC)			Optional
RC Switching Capacity			AC: 250 V/0.5 A, 125 V/0.1 A; DC: 48 V/0.5 A, 24 V/0.5 A, 12 V/0.5 A
RC Conductor Cross Section (max)			16 AWG (Solid)/1.5 mm² (Solid)
Overvoltage Category			III


Raycap


Information contained in this document is subject to change at any time without notice.
No part of this document may be reproduced or used without written permission from Raycap.

Internal Configuration

Legend

L	*Line Conductor Terminal*
N	*Neutral Conductor Terminal*
⏚	*PE Conductor Terminal*
RC	*Remote Contacts Terminal (Optional)*
TD	*Thermal Disconnector*






Order Information	
Order Code	**275**
ProTec T1SM-xxx-4+0	59.D135
ProTec T1SM-xxx-4+0-R (with remote contacts)	59.D136
ProTec T1SM-xxx-4+0-P (plug)	59.D140


Dimensions & Packaging

inches [mm]



Complete Unit		
ProTec T1SM-xxx-4+0		**275**
Weight	pounds [grams]	.950 [431]
ProTec T1SM-xxx-4+0-R		
Weight	pounds [grams]	.962 [436]
DIN 43880 Dimension		4 TE/2.84 [72 mm]
Packaging Dimensions (H x W x L)		4.3 × 4.5 × 13.8" [109 × 115 × 352 mm]
Standard Order Quantity		4 Units

Spare Plug



Single Unit		
ProTec T1SM-xxx-4+0-P		**275**
Weight	pounds [grams]	.419 [190]
DIN 43880 Dimension		4 TE/2.84 [72 mm]
Packaging Dimensions (H x W x L)		3.1 × 4.5 × 12" [80 × 115 × 305 mm]
Standard Order Quantity		7 Units

© 2026 Raycap All rights reserved.